

JOISTRITE WORK SHEET

TOLL FREE: 1.866.545.1545 PHONE: 770.507.2600 FAX: 770.507.2605

e-mail: technicalservices@marinoware.com

COMPANY NAME & CONTACT PERSON	PHONE & FAX
PROJECT NAME & LOCATION	DATE
	JOISTRITE RIM TRACK
END BEARING WIDTH (IN INCHES) Span #1 (ft-in) Dead Load (psf) Live Load (psf) Span #2 (ft-in) Dead Load (psf) Live Load (psf) Span #3 (ft-in) Dead Load (psf) Live Load (psf) Live Load (psf) Live Load (psf)	JOISTRITE MEMBER SIZE & SPACING
* THE SPAN IS FROM CENTERLINE OF BEARING, * STRAPPING AND BLOCKING REQUIRED EVERY 7'-0" O.C.	
* MAXIMUM JOIST DEPTH = * DESIRED JOIST SPACING = * TOTAL LOAD DEFLECTION = L/240 * LIVE LOAD DEFLECTION = L/360 OR L/480 SUGGESTED DEAD & LIVE LOADS (REFERENCE):	FIRE RATED INFORMATION: * NON-RATED FLOOR: YES NO * FIRE RATED FLOOR: WHI Intertek 3101528 - 1 Hour with Plywood WHI Intertek 3099463 - 1.50 Hour with Viroc UL # G563 - 2 Hour with Maxxon UL # L580 - 1 Hour with Plywood Other
DEAD LOAD (PSF)	LIVE LOAD (PSF) RESIDENTIAL: TYPICAL ROOM = 40 SLEEPING ROOM = 30 OTHER =